


## GENERAL SPECIFICATION SHEET

### PTFE-PTFE-SS BRAIDING

**UP TO 260 DEG C**



Cold-resistant



Single halogen-free cable



Temperature-resistant

### Technical Detail


<b>Design Standard</b>	: As per JSS 51034, IS 8130
<b>Conductor</b>	: Annealed Bare Copper / Nickel Plated Copper / Silver Plated Copper
<b>Conductor Size</b>	: Variant as per customer specifications
<b>Conductor Type</b>	: Solid wire / Flexible
<b>No of Core</b>	: Single Core / Multi Core
<b>Core Insulation</b>	: Wrapped & Sintered PTFE( Teflon ) Insulation
<b>Core Formation</b>	: Twisted / Flat
<b>Inner Sheath Insulation</b>	: Wrapped & Sintered PTFE( Teflon ) Insulation
<b>Outer Sheath Insulation</b>	: Stainless Steel Wire Braiding / Armouring
<b>Core Colour</b>	: As per Customer specification.
<b>Outer Sheath Colour</b>	: As per Customer specification.
<b>Cable Temp. Range</b>	: Up to 260 Deg C
<b>Voltage Grade</b>	: Upto 1100 V

### **Special Features**

Max. Temp. upto 260°C  
Excellent Heat Resistant  
Outstanding Insulating Properties  
Good Thermal Stability  
Flame Retardant  
Excellent Mechanical Strength  
Passes JSS 51034 Flame Test

**TECHNICAL ( GA ) DRAWING**

ABC / NPC / SPC CONDUCTOR

**HIGH TEMPERATURE CABLE**