


GENERAL SPECIFICATION SHEET

PTFE-KAPTON-PTFE-MICA-FG-ASBESTOS BRAIDING

UP TO 600 DEG C



Cold-resistant



Single halogen-free cable




Temperature-resistant

Technical Detail

Design Standard	: As per JSS 51034, IS 8130
Conductor	: Annealed Bare Copper / Nickel Plated Copper / Silver Plated Copper
Conductor Size	: Variant as per customer specifications
Conductor Type	: Solid wire / Flexible
No of Core	: Single Core / Multi Core
Core Insulation (A)	: Wrapped & Sintered PTFE(Teflon) Insulation
Core Formation	: Twisted
Overall Isolator	: Kapton Tapping
Inner Sheath Insulation	: Wrapped & Sintered PTFE(Teflon) Insulation
High Temp. Tapping	: Mica Tapping
Overall Braiding	: Fiber Glass Braiding
Overall Braiding	: Asbestos Braiding
Core Colour	: As per Customer specification.
Outer Sheath Colour	: As per Customer specification.
Cable Temp. Range	: Up to 600 Deg C
Voltage Grade	: Upto 1100 V

Special Features

Max. Temp. upto 600°C
 Excellent Heat Resistant
 Outstanding Insulating Properties
 Good Thermal Stability
 Flame Retardant
 Good Abrasion Resistance
 Good Dielectric Strength
 Passes JSS 51034 Flame Test

TECHNICAL (GA) DRAWING**HEAT RESISTANCE CABLE**